



US006469683B1

(12) **United States Patent**
Suyama et al.

(10) Patent No.: **US 6,469,683 B1**
(45) Date of Patent: ***Oct. 22, 2002**

(54) **LIQUID CRYSTAL OPTICAL DEVICE**

FOREIGN PATENT DOCUMENTS

(75) Inventors: **Shiro Suyama, Tokyo; Munekazu Date, Sayama; Shigeto Kohda, Chofu; Kinya Kato, Iruma; Shigenobu Sakai, Tama, all of (JP)**

JP 54-101344 9/1979
JP 54-101345 9/1979

OTHER PUBLICATIONS

(73) Assignee: **Nippon Telegraph and Telephone Corporation, Tokyo (JP)**

(*) Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

Masakatsu Higa, et al, "A High-Speed and High-Contrast Liquid-Crystal Shutter Array Using Dual-Frequency Addressed Birefringence Mode", May 1989, SID International Symposium, Digest of Technical Papers, Baltimore, MD, USA, pp. 25-28.

Masakatsu Higa et al., "A High-Speed and High Contrast Liquid-Crystal Shutter Array Using Dual-Frequency Addressed Bire-fringence Mode", 1989, pp. 25-28, 427.

Science Research Expenditure Subsidy Research Results Report No. 5980048, Susumu Sato et al. Variable-Focus Liquid-Crystal Fresnel Lens, pp. 626-628, 1985.

(21) Appl. No.: **08/784,353**

(22) Filed: **Jan. 16, 1997**

(30) **Foreign Application Priority Data**

Jan. 17, 1996	(JP)	8-006011
Mar. 5, 1996	(JP)	8-047654
May 1, 1996	(JP)	8-110632
Jul. 11, 1996	(JP)	8-182222
Jul. 31, 1996	(JP)	8-202244
Aug. 30, 1996	(JP)	8-229717

(51) Int. Cl.⁷ **G09G 3/00**

(52) U.S. Cl. **345/32; 345/6; 349/62; 349/64**

(58) Field of Search **345/32, 6-8, 87, 345/99, 205, 212; 349/36, 63, 135**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,037,929 A	7/1977	Bricott et al.
4,564,267 A	1/1986	Nishimoto
4,729,641 A	3/1988	Matsuoka et al.
4,781,440 A	11/1988	Toda
5,493,427 A	2/1996	Nomura et al.

Primary Examiner—Steven Saras

Assistant Examiner—Amr Awad

(74) *Attorney, Agent, or Firm*—Venable; Robert J. Frank

(57) **ABSTRACT**

An optical device includes a transparent layer having a desired curved surface configuration, a layer including a variable refractive index material having a dielectric constant anisotropy, at least two transparent electrodes arranged to sandwich the transparent material layer and the variable refractive index material, and a driving device supplying a voltage including driving frequencies f_1 and f_2 between the transparent electrodes. The difference $\Delta\epsilon$ in the dielectric constant of the variable refractive index material due to the anisotropy is positive at one of the driving frequencies and negative at the driving frequency.

20 Claims, 67 Drawing Sheets

